

Week 7 – part 3 :Spike Response Model (SRM)



Neuronal Dynamics: Computational Neuroscience of Single Neurons

Week 7 – Optimizing Neuron Models For Coding and Decoding

Wulfram Gerstner

EPFL, Lausanne, Switzerland

7.1 What is a good neuron model?

- Models and data

7.2 AdEx model

- Firing patterns and analysis

7.3 Spike Response Model (SRM)

- Integral formulation

7.4 Generalized Linear Model

- Adding noise to the SRM

7.5 Parameter Estimation

- Quadratic and convex optimization

7.6. Modeling *in vitro* data

- how long lasts the effect of a spike?

7.7. Helping Humans

Week 7 – part 3 :Spike Response Model (SRM)



7.1 What is a good neuron model?

- Models and data

7.2 AdEx model

- Firing patterns and analysis

7.3 Spike Response Model (SRM)

- Integral formulation

7.4 Generalized Linear Model

- Adding noise to the SRM

7.5 Parameter Estimation

- Quadratic and convex optimization


7.6. Modeling in vitro data

- how long lasts the effect of a spike?


7.7. Helping Humans

Exponential versus Leaky Integrate-and-Fire

$$\tau \frac{du}{dt} = -(u - u_{rest}) + \Delta \exp\left(\frac{u - \vartheta}{\Delta}\right) + RI(t)$$



Badel et al (2008)



$$\tau \frac{du}{dt} = -(u - u_{rest}) + RI(t)$$

Leaky Integrate-and-Fire

Reset if $u = \vartheta$

Neuronal Dynamics – 7.3 Adaptive leaky integrate-and-fire

$$\begin{aligned}\tau \frac{du}{dt} &= -(u - u_{rest}) - R \sum_k w_k + RI(t) \\ \tau_k \frac{dw_k}{dt} &= a_k (u - u_{rest}) - w_k + b_k \tau_k \sum_f \delta(t - t^f)\end{aligned}$$

SPIKE AND RESET

after each spike
 w_k jumps by an amount b_k
If $u = \vartheta(t)$ then reset to $u = u_r$

Dynamic threshold

Neuronal Dynamics – 7.3 Adaptive leaky I&F and SRM

$$\begin{aligned}\tau \frac{du}{dt} &= -(u - u_{rest}) - R \sum_k w_k + RI(t) \\ \tau_k \frac{dw_k}{dt} &= a_k(u - u_{rest}) - w_k + b_k \tau_k \sum_f \delta(t - t^f)\end{aligned}$$

Adaptive
leaky I&F


Linear equation → can be integrated!

$$u(t) = \sum_f \eta(t - t^f) + \int_0^\infty ds \kappa(s) I(t - s)$$

$$\vartheta(t) = \theta_0 + \sum_f \theta_1(t - t^f)$$


Spike Response Model (SRM)
Gerstner et al. (1996)

Neuronal Dynamics – 7.3 Spike Response Model (SRM)




Neuronal Dynamics – 7.3 Bursting in the SRM

SRM with appropriate η leads to bursting



$$u(t) = \sum_f \eta(t - t^f) + \int_0^\infty ds \kappa(s) I(t - s) + u_{rest}$$

Neuronal Dynamics – 7.3 Spike Response Model (SRM)



potential

$$u(t) = \sum_{t'} \eta(t - t') + \int_0^\infty \kappa(s) I(t - s) ds + u_{rest}$$

threshold

$$\vartheta(t) = \theta_0 + \sum_{t'} \theta_1(t - t')$$


firing if

$$u(t) = \vartheta(t)$$

Neuronal Dynamics – 7.3 Spike Response Model (SRM)

potential

$$u(t) = \sum_{t'} \eta(t - t') + \int_0^\infty \kappa(s) I(t - s) ds + u_{rest}$$




threshold

$$\vartheta(t) = \theta_0 + \sum_{t'} \theta_1(t - t')$$

Linear filters for
- input
- threshold
- refractoriness

Neuronal Dynamics – 7.3 Spike Response Model (SRM)



Linear filters for

- input
- threshold
- refractoriness